PATENT SPECIFICATION (11)1 558 491 PATENT SPEC.

1. to currence to DE 25, 39, 132

(21) Application No. 35969/76 (2)

(31) Convention Application No. 2539132

(22) Filed 31 Aug. 1976

(32) Filed 3 Sep. 1975 in

(33) Fed. Rep. of Germany (DE)

(44) Complete Specification Published 3 Jan. 1980

(51) INT. CL.<sup>3</sup>

30

C08C 19/02 C08F 8/04

RUDOLPH BRADEN

(52) Index at Acceptance C3J AH

(72) Inventors: DIETER OPPELT HERBERT SCHUSTER JOACHIM THORMER



## (54) HYDROGENATION OF POLYMERS

(71) We, BAYER AKTIENGESELLSCHAFT, of 509 Leverkusen, Germany, a body corporate organised under the laws of Germany, do hereby declare the invention, for which we pray that a patent may be granted to us, and the method by which it is to be performed, to be particularly described in and by the following statement:

This invention relates to a process for the production of partially hydrogenated copolymers of an  $\alpha,\beta$ -unsaturated carboxylic acid or derivatives thereof and a hydrocarbon

containing conjugated double bonds.

Random copolymers of monomers such as these are known from German Patent Specifications Nos. 570,980 and 658,172. They are obtained by the emulsion copolymerisa-

tion of, for example, acrylonitrile with conjugated dienes, such as butadiene.

It is known from US-PS 3,700,637 that regularly alternating copolymers can be produced from butadiene and acrylonitrile and can be hydrogenated by means of rhodium complexes

as catalysts with the nitrile groups left intact.

In the context of the present invention, copolymers are both regularly alternating and also random copolymers of an  $\alpha.\beta$ -unsaturated carboxylic acid or derivative thereof and an unsaturated hydrocarbon containing conjugated double bonds. The back-bone of the copolymer consists entirely of carbon atoms.

Suitable carboxylic acids and their derivatives are, for example, (meth)acrylic acid, fumaric acid, their esters and amides, and also the corresponding carboxylic acid nitriles, such as (meth)acrylonitrile. Suitable conjugated dienes are, for example, butadiene, isoprene, dimethyl butadiene and piperylene. The process according to the invention is preferably used for the partial hydrogenation of copolymers of (meth)acrylic acid or derivatives thereof and butadiene. Copolymers of 90 to 45% by weight of butadiene and 10 to 55% by weight of acrylonitrile (based in each case on the copolymer total) are particularly preferred.

-In addition to the functional groups emanating from the carboxylic acid or its derivatives, for example the nitrile group, unsaturated structural units present in the above-mentioned copolymers are the vinyl groups formed during 1,2-bonding of the dienes used and the cis-

or trans-configuration olefinic double bonds formed during 1.4-bonding. According to the invention, the copolymers are dissolved in suitable organic solvents and are hydrogenated in the presence of a rhodium complex and, optionally, a ligand of the complex, e.g. triphenyl phosphine, at elevated temperature and pressure with any other functional groups, e.g. the nitrile group, left intact. In this connection, it has surprisingly been found that, in cases where chlorobenzene is used as solvent, the vinyl groups and the trans-configuration double bonds in the above-mentioned copolymers are completely hydrogenated in a selective manner. If on the other hand other solvents are used, the vinyl groups are completely hydrogenated, whereas the trans-configuration double bonds are only partially hydrogenated. The degree of hydrogenation of the trans-configuration double bonds amounts to between 10 and 90 %, based on the quantity of these double bonds,

depending upon the solvent used. It was by no means foreseeable to the expert that the controlled use of certain solvents in a hydrogenation reaction carried out under identical conditions would enable the vinyl groups to be completely hydrogenated and the trans-configuration double bond to be completely or partially hydrogenated in a selective

The present invention relates to a process for selective hydrogenation of the vinyl groups 45

25

10

15

20



60

and trans-configuration double bonds in copolymers of an α,β-unsaturated carboxylic acid or a derivative thereof and an unsaturated hydrocarbon containing conjugated double bonds, the back-bone of the copolymer consisting entirely of carbon atoms, distinguished by the fact that a 1 to 20 % solution of the copolym r in a suitable organic solvent is hydrogenated at 50 to 150°C and at 5 to 300 atms (absolute pressure) in the presence of 0.01 to 10 % by weight of a catalyst of a complex compound of a monovalent or trivalent rhodium halide, and, optionally, 5 to 25 % by weight of the ligand bound in the complex (based in each case on dissolved copolymer). Selective hydrogenation of the vinyl groups and trans-configuration double bonds in the copolymers may be carried out in a chlorine-substituted aromatic solvent with from 6 to 12 carbon atoms, preferably 10 chlorobenzene, as solvent. In this medium the polar groups (for example nitrile groups) do not undergo any demonstrable hydrogenation. If solutions of the copolymers in other solvents, such as for example toluene, benzene, xylene, dimethyl formamide, ethyl acetate, methyl ethyl ketone, tetrahydrofuran, cyclohexanone or methylene chloride, are used in accordance with the invention, complete hydrogenation of the vinyl groups is accompanied 15 by only partial hydrogenation of the trans-configuration double bonds. The degree of hydrogenation of these double bonds is governed by the type of solvent used and decreases from around 90 to about 10 % in the order benzene > dimethylformamide = xylene > ethyl acetate > toluene > methyl ethyl ketone > cyclohexanone > tetrahydrofuran > methylene chloride. Although not necessary, it is of course also possible 20 20 to use solvent mixtures for the process according to the invention.

The solutions contain from 1 to 20 % by weight and preferably from 2.5 to 10 % by weight of the copolymers, based on the particular above-described solvent used for the process according to the invention. From 0.01 to 10 % by weight and preferably from 0.1 to 5 % by weight (based on the 25 25 dissolved copolymer) of a complex compound of monovalent or trivalent rhodium halides are added to the solutions of the copolymers as a catalyst for the hydrogenation reaction. Suitable complex compounds correspond to the general formula (I):  $(R_m B)_3 Rh X_n$  (I) 30 30 in which  $R = C_1-C_8$  alkyl,  $C_6-C_{15}$  aryl or  $C_7-C_{15}$  aralkyl, B = P. As, S or S=0, X = C1 or Br, = 2 or 3, and 35 35 = 1 or 3.Preferred complex compounds of this type are tris-(triphenyl phosphine)-rhodium(I)chloride. tris-(triphenyl phosphine)-rhodium(III)-chloride and tris-(dimethyl sulphoxide)rhodium(III)-chloride. 40 The pressure under which the hydrogenation reaction according to the invention is carried out may be varied within a wide range. Suitable pressures are in the range of from 5 to 300 atms and preferably in the range of from 50 to 100 atms. The hydrogenation reaction is carried out at temperatures in the range of from 50 to 150°C, and preferably at temperatures in the range of from 75 to 115°C. Under these conditions, the selective 45 hydrogenation reaction is over after about 3 to 7 hours. The catalyst may be separated off by the method described in DT-AS 1,558,395. The hydrogenation product is separated off from the reaction solution by treatment with steam or by pouring into methanol and is subsequently dried under reduced pressure at a temperature of approximately 70°C.

Qualitative and quantitative determination of the hydrogenated double bonds and 50 double bonds still present in the copolymers hydrogenated in accordance with the invention is carried out by IR-spectroscopic analysis. For further characterisation the iodine number and the glass transition temperature of the hydrogenation products are determined (in case of the glass transition temperature by thermomechanical analysis (TMA) and shear 55 modulus measurement). The copolymers hydrogenated by the process according to the invention show increased tensile strength for increased elongation at break and, in addition, improved elasticity.

They are vulcanisable rubbers which may be used as temperature-resistant materials, for

example in the sealing field.

Three different acrylonitrile-butadiene copolymers are used in the following Examples. The percentages quoted are always per cent by weight.

The quantities of catalysts and triphenyl phosphine quoted in the Examples are based in each case on the dissolved copolymer.

5.	Copolymer I: of 82% of butadien Copolymer II: of 72% of butadien Copolymer III: of 62% of butadien (based in each case on the copolymer)	ne and 28% of acrylonitrile ne and 38% of acrylonitrile	5
10	copolymer I in chlorobenzene, followed On completion of hydrogenation, the 1.558,395. The reaction products are p	of $(C_6H_5)_3P$ are added to a 2.5% solution of by hydrogenation for 5.5 hours at 100°C/60 atms. catalyst is separated off in accordance with DT-AS precipitated by pouring the reaction solution into under reduced pressure at approximately 70°C. d has the following properties:	10
15	Degree of hydrogenation: Glass transition temperature:	100% of the vinyl and 100% of the trans-double bonds $T_{\sigma} = -31^{\circ}C$	15
20	Iodine Number:	IÑo. = 14  llowing Examples are worked up and characterised	20
25	Example 2 1% of [(C <sub>6</sub> H <sub>5</sub> ) <sub>3</sub> P] Rh <sup>1</sup> Cl and 10% of (I in chlorobenzene, followed by hydrogenation product has the	C <sub>6</sub> H <sub>5</sub> ) <sub>3</sub> P are added to a 2.5% solution of copolymer rogenation for 4.5 hours at 100°C/60 atms. following properties:	25
30 ·	Degree of hydrogenation: Glass transition temperature: Iodine Number:	100% of the vinyl and 100% of the trans-double bonds $T_g = -30^{\circ}C$ INo. = 26	30
35°	Example 3 1% of [(C <sub>6</sub> H <sub>5</sub> ) <sub>3</sub> P] <sub>3</sub> Rh <sup>III</sup> Cl <sub>3</sub> and 10% copolymer II in chlorobenzene, followed The hydrogenation product has the	% of $(C_6H_5)_3P$ are added to a 2.5% solution of d by hydrogenation for 5.5 hours at 100°C/60 atms. following properties:	35
40°'	Degree of hydrogenation: Glass transition temperature: Iodine number:	100% of the vinyl— and 100% of the trans-double bonds $T_g = -30^{\circ}C$ IN 0. = 22	40
45	Example 4 1% of [(C <sub>6</sub> H <sub>5</sub> ) <sub>3</sub> P] <sub>3</sub> Rh <sup>I</sup> Cl and 10% of (III in chlorobenzene, followed by hydrogenation product has the	C <sub>6</sub> H <sub>5</sub> ) <sub>3</sub> P are added to a 2.5% solution of copolymer lrogenation for 6 hours at 100°C/60 atms. following properties:	45
50 ·	Degree of hydrogenation: Glass transition temperature: Iodine Number:	100% of the vinyl- and 100% of the trans-double bonds $T_c = -27^{\circ}C$ INo. = 22	50
55	Example 5 1% of [(C <sub>6</sub> H <sub>5</sub> ) <sub>3</sub> P] <sub>3</sub> Rh <sup>I</sup> Cl and 10% copolymer I in the toluene, followed be The hydrogenation product has the	of $(C_6H_5)_3P$ are added to a 2.5% solution of by hydrogenation for 4.5 hours at 100°C/60 atms. following properties:	55
60	Degree of hydrogenation: Glass transition temperature:	100% of the vinyl- and 48% of the trans-double bond $T_g = -43^{\circ}C$	60
65	Iodine Number:	IÑo. = 50	65

_	Example 6 1% of [(C <sub>6</sub> H <sub>5</sub> ) <sub>3</sub> P] <sub>3</sub> Rh <sup>I</sup> Cl and 10% copolymer II in the toluene, followed The hydrogenation product has the	of $(C_6H_5)_3P$ are added to a 2.5% solution of by hydrogenation for 5.2 hours at 100°C/60 atms. following properties:	5
5	Degree of hydrogenation:	100% of the vinyl— and 42% of the trans-double bonds	J
1Ö·	Glass transition temperature: Iodine Number:	$T_g = -26^{\circ}C$ $INo. = 95$	10
15	Example 7 1% of [(C <sub>6</sub> H <sub>5</sub> ) <sub>3</sub> P] <sub>3</sub> Rh <sup>t</sup> Cl and 10% (Cl III in toluene, followed by hydrogena The hydrogenation product has the	$(G_6H_5)_3P$ are added to a 2.5% solution of copolymeration for 5 hours at 100°C/60 atms. following properties:	15.
	Degree of hydrogenation:	100% of the vinyl- and 30% of the	
20	Glass transition temperature: Iodine number:	trans-double bonds $T_g = -26^{\circ}C$ INo. = 60	20
25	Example 8 1% of [(CH <sub>3</sub> ) <sub>2</sub> S=0] <sub>3</sub> Rh <sup>III</sup> Cl <sub>3</sub> and 10 copolymer II in chlorobenzene, followed The hydrogenation product has the	% of (CH <sub>3</sub> ) <sub>2</sub> S=0 are added to a 2.5% solution of d by hydrogenation for 7.5 hours at 100°C/60 atms. following properties:	25
	Degree of hydrogenation:	100% of the vinyl- and 100% of	
30	Glass transition temperature: Iodine number:	the trans-double bonds $T_g = -29^{\circ}C$ INo. = 29	30
35	Example 9 1% of [(C <sub>6</sub> H <sub>5</sub> ) <sub>3</sub> P] <sub>3</sub> Rh <sup>III</sup> Cl <sub>3</sub> and 10% copolymer II in benzene, followed by The hydrogenation product has the	% of $(C_6H_5)_3P$ are added to a 2.5% solution of hydrogenation for 6.2 hours at 100°C/60 atms. following properties:	35
40 <sup>.</sup>	Degree of hydrogenation: Glass transition temperature: Iodine number:	100% of the vinyl— and 90% of the trans-double bonds $T_g = -30^{\circ}C$ INo. = 19	40
	Journe number.		
45	Example 10 1% of [(C <sub>6</sub> H <sub>5</sub> ) <sub>3</sub> P] <sub>3</sub> Rh <sup>I</sup> Cl and 10% copolymer II in ethyl acetate, followed The hydrogenation product has the	of $(C_6H_5)_3P$ are added to a 2.5% solution of by hydrogenation for 5.5 hours at 100°C/60 atms. following properties:	45
50	· · · · · · · · · · · · · · · · · · ·	100% of the vinyl— and 50% of the	50
	Glass transition temperature: Iodine number:	trans-double bonds $T_g = -38^{\circ}C$ INo. = 77	
55			55
	copolymer II in methyl ethyl ketone, for	of $(C_6H_5)_3P$ are added to a 2.5% solution of bllowed by hydrogenation for 6 hours at $100^{\circ}C/60$	
60	atms.  The hydrogenation product has the	following properties:	60
	Degree of hydrogenation:	100% of the vinyl— and 40% of the trans-double bonds	
65	Glass transition temperature: Iodine number:	$T_g = -39^{\circ}C$ INo. = 119	65
-			

5

10

20

30

35 35 1% of [(C<sub>6</sub>H<sub>5</sub>)<sub>3</sub>P]<sub>3</sub> Rh<sup>I</sup>Cl and 10% of (C<sub>6</sub>H<sub>5</sub>)<sub>3</sub>P are added to a 2.5% solution of copolymer II in tetrahydrofuran, followed by hydrogenation for 3.2 hours at 100°C/60 atms. The hydrogenation product has the following properties:

40 40 Degree of hydrogenation: 100% of the vinyl- and 31% of the trans-double bonds  $T_g = -39^{\circ}C$ INo. = 113 Glass transition temperature: Iodine number:

45 Example 16 1% of  $[(C_6H_5)_3P]_3$  Rh<sup>1</sup>Cl and 10% of  $(C_6H_5)_3P$  are added to a 2.5% solution of copolymer II in methylene chloride, followed by hydrogenation for 6.5 hours at 100°C/60 50 The hydrogenation product has the following properties:

Degree of hydrogenation: 100% of the vinyl- and 12% of the trans-double bonds

50

 $T_g = -40^{\circ}C$ Glass transition temperature: 55 Iodine number: 55

The results of Examples 1 to 16 are summarised in Table 1 below:

•	
	_
	Щ
	TABLE
	$\succeq$

$T_{g}$		:
ponds		
unyl- trans-double bonds	850 842 860 860 860 860 860 860 860 860 860 860	
%) vinyl–	888888888888888888888888888888888888888	
Degree of hydrogenation(%) Catalyst	[(C <sub>6</sub> H <sub>5</sub> ) <sub>3</sub> P] <sub>3</sub> Rh <sup>1</sup> Cl [(C <sub>6</sub> H <sub>5</sub> ) <sub>3</sub> P] <sub>3</sub> Rh <sup>11</sup> Cl [(C <sub>6</sub> H <sub>5</sub> ) <sub>3</sub> P] <sub>3</sub> Rh <sup>11</sup> Cl [(C <sub>6</sub> H <sub>5</sub> ) <sub>3</sub> P] <sub>3</sub> Rh <sup>11</sup> Cl <sub>3</sub> [(C <sub>6</sub> H <sub>5</sub> ) <sub>3</sub> P] <sub>3</sub> Rh <sup>11</sup> Cl <sub>3</sub> [(C <sub>6</sub> H <sub>5</sub> ) <sub>3</sub> P] <sub>3</sub> Rh <sup>1</sup> Cl <sub>3</sub>	
Solvent	chlorobenzene " " " chlorobenzene benzene ethyl acetate methyl ethyl ketone xylene dimethyl formamide cyclohexanone tetrahydrofuran methylene	chloride
Co- polymer		
Example		

	WHAT WE CLAIM IS:	
5	1. A process for the selective hydrogenation of the vinyl groups and trans-configuration double bonds in a copolymer of an α,β-unsaturated carb xylic acid or a derivative thereof and an unsaturated hydrocarbon containing conjugated double bonds, the back-bone of the copolymer c nsisting entirely of carbon atoms, which comprises hydrogenating a 1 to 20% solution of the copolymer in an organic solvent at a temperature of fr m 50 to 150°C and at pressure of from 5 to 300 atmospheres in the presence of from 0.01 to 10% by weight of a complex of a monovalent or trivalent rhodium halide as a catalyst and, optionally, from 5 to	5
10	25% by weight of the ligand bound in the complex (based in each case on the dissolved copolymer).	10
15	2. A process as claimed in Claim 1, wherein the solvent is a chlorine-substituted aromatic solvent with from 6 to 12 carbon atoms, and the vinyl groups and the trans-configuration double bonds are completely hydrogenated in a selective manner.  3. A process as claimed in Claim 1, wherein the solvent is toluene, benzene, ethyl acetate, methyl ethyl ketone, xylene, dimethyl formamide, cyclohexanone, tetrahydrofuran or methylene chloride, and from 10 and 90% of the trans-configuration double bonds, in addition to the vinyl groups, are hydrogenated, depending upon the solvent used.	15
20	4. A process as claimed in any of Claims 1 to 3, wherein the copolymer to be hydrogenated is a copolymer of (meth)acrylic acid, an ester or amide thereof or (meth)acrylonitrile, with butadiene, isoprene, dimethyl butadiene or piperylene.  5. A process as claimed in any of Claims 1 to 4, wherein the copolymer is a butadiene-acrylonitrile copolymer of from 90 to 45% by weight of butadiene and from 10 to 55% by weight of acrylonitrile (based in each case on the copolymer total).	20
25	6. A process as claimed in any of claims 1 to 5, wherein the complex corresponds to the general formula (I):	25
	$(R_mB)_3$ Rh $X_n$ (I)	
30	in which $R = C_1-C_8$ alkyl, $C_6-C_{15}$ aryl or $C_7C_{15}$ aralkyl, B = P, As, S or S=0, X = Cl or Br, m = 2 or 3, and n = 1 or 3.	30
35	<ul> <li>7. A process as claimed in any of Claims 1 to 6, wherein the hydrogenation is carried out in the presence of from 0.1 to 5% of the complex.</li> <li>8. A process as claimed in any of Claims 1 to 7, wherein the hydrogenation temperature</li> </ul>	35
40	is from 75 to 115°C.  9. A process as claimed in any of Claims 1 to 8, wherein the hydrogenation pressure is from 50 to 100 atmospheres.  10. A process as claimed in any of claims 1 to 9, wherein the rhodium complex has sulphur-containing ligands.	40
45	11. A process as claimed in Claim 1, substantially as herein described with reference to any of the specific Examples.  12. A copolymer when hydrogenated by a process as claimed in any of Claims 1 to 11.	45
50	ELKINGTON & FIFE. Chartered Patent Agents. High Holborn House, 52/54 High Holborn, London WCIV 6SH. Agents for the Applicants.	50